



|                               |                    |
|-------------------------------|--------------------|
| <b>Model</b>                  | <b>30D</b>         |
| <b>Part #</b>                 | 52000              |
| <b>Agent Capacity</b>         | 30 lb. (13.6 kg)   |
| <b>FM Rating</b>              | D                  |
| <b>Discharge Time</b>         | 28 sec             |
| <b>Operating Pressure</b>     | 195 psi (1344 kPa) |
| <b>Mounting Type</b>          | Wall               |
| <b>USCG Approval</b>          | N/A                |
| <b>Ship Weight</b>            | 55 lb. (24.95 kg)  |
| <b>Unit Height</b>            | 33 in (83.8 cm)    |
| <b>Unit Width (Incl Hose)</b> | 16 in (40.6 cm)    |
| <b>Unit Diameter</b>          | 8 in (20.3 cm)     |



## Combustible Metals - Class D

Specifically designed for use on combustible metal fires, this extinguisher features a discharge assembly that keeps the operator at a safe distance while providing accurate application of the agent on the fire.

From the heat of the fire, the sodium chloride based agent forms a crust to exclude air from the burning material. Suitable for use on Class D fires such as those involving magnesium, sodium, potassium and sodium-potassium alloys.

There is data showing that zirconium, uranium, titanium, and powdered aluminum fires can be controlled and extinguished with this unique extinguisher.

**Typical Uses:** Metal production and machining operations.

